

More safety clamps with aseptic connections according to DIN 11864 (-1,-2,-3) in pipe series A, B and C.

Our fittings are made of stainless steel according to DIN 11864-1, optionally in hygiene classes H3 or H4



### Safety clamps PN 25

According to EN 14420 with aseptic liner, according to DIN 11864-1, pipe series A with union nuts

Article	DN	Thread
ASM13A	13	Rd. 34x1/8"
ASM19A	19	Rd. 44x1/6"
ASM25A	25	Rd. 52x1/6"
ASM32A	32	Rd. 58x1/6"
ASM38A	38	Rd. 65x1/6"
ASM50A	50	Rd. 78x1/6"
ASM65A	63	Rd. 95x1/6"
ASM75A	75	Rd. 110x1/4"
ASM100A	100	Rd. 130x1/4"



### Safety clamps PN 25

according to EN14420 with aseptic threaded connector according to DIN 11864-1, pipe series A

Article	DN	Thread
ASV13A	13	Rd. 34x1/8"
ASV20A	19	Rd. 44x1/6"
ASV25A	25	Rd. 52x1/6"
ASV32A	32	Rd. 58x1/6"
ASV38A	38	Rd. 65x1/6"
ASV50A	50	Rd. 78x1/6"
ASV65A	63	Rd. 95x1/6"
ASV75A	75	Rd. 110x1/4"
ASV100A	100	Rd. 130x1/4"



**Safety clamps PN 10 to PN 25** nominal width-dependent, according to EN 14420 with aseptic collar flange according to DIN 11864-2, pipe series A

Article	DN	Flange size [mm]
ASFB13A	13	59.0
ASFB19A	19	64.0
ASFB25A	25	70.0
ASFB32A	32	76.0
ASFB38A	38	82.0
ASFB50A	50	94.0
ASFB65A	63	113.0
ASFB75A	75	133.0
ASFB100A	100	159.0



**Safety clamps PN 10 to PN 25** nominal width-dependent, according to EN 14420 with aseptic groove flange according to DIN 11864-2, pipe series A

Article	DN	Flange size [mm]
ASFN13A	13	59.0
ASFN19A	19	64.0
ASFN25A	25	70.0
ASFN32A	32	76.0
ASFN38A	38	82.0
ASFN50A	50	94.0
ASFN65A	63	113.0
ASFN75A	75	133.0
ASFN100A	100	159.0



**Safety clamps, PN 16 to PN 40** according to EN 14420 with aseptic clamp ferrule with groove according to DIN 11864-3

Article	DN
ASNKS13A	13
ASNKS20A	19
ASNKS25A	25
ASNKS32A	32
ASNKS38A	38
ASNKS50A	50
ASNKS65A	63
ASNKS75A	75
ASNKS100A	100



**Safety clamps PN 16 to PN 40** according to EN14420 with aseptic clamp ferrule according to DIN 11864-3

Article	DN
ASBK13A	13
ASBK19A	19
ASBK25A	25
ASBK32A	32
ASBK38A	38
ASBK50A	50
ASBK65A	63
ASBK75A	75
ASBK100A	100